

DE-COMP COMPOSITES, INC.

D230

BAGGING FILM

D230 is a bagging film that is highly recommended to be used for any application where high elongation, good tear resistance, and excellent air retention is required. This film is rated for temperatures up to 300°F/149°C.

Due to the fact that D230 has excellent drape and flexibility, and releases easily, this film may be used multiple times.

Typical applications include but are not limited to, retaining hot materials, vacuum forming, protective coverings, and use as a release film.

PROPERTIES

Tensile Strength (psi)	3,720
Elongation (%)	550
Maximum Use Temperature	300°F/149°C
Melt Temperature	340°F/171°C
Thickness (inches)	0.002
Width (inches)	36" Sheet
Yield (ft ² /lb)	93
Color	Yellow Tint

Note: Other sizes are available upon request.

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.