

DE-COMP COMPOSITES, INC.

D2919

BAGGING FILM

D2919 is a high-temperature, fluoropolymer, polyamide cast film. D2919 is an excellent film for bagging high temperature parts such as BMI, PI, and phenolic resin systems.

PROPERTIES

Color	Natural
Tensile Strength (psi)	18,000
Elongation (%)	100
Elastic Modules (psi)	250,000
Coefficient of Friction	.340
Tear Resistance (pli)	1,000
Maximum Use Temperature	600°F / 315°C
Thickness (inches)	.002
Widths (inches)	48
Yield (ft ² /lb	54

SUGGESTED STORAGE METHOD:

All nylon films are known to be hydrophilic. They absorb up to 2.5% of surrounding humidity, therefore, it is recommended that this film be kept in a sealed plastic bag.

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.