

# DE-COMP COMPOSITES, INC.

## D6600

### HIGH-TEMP BAGGING FILM

D6600 is a high temperature fluorocarbon polyamide cast film. D6600 is an excellent film for bagging high temperature parts such as BMI, PI and phenolic resin systems.

#### PROPERTIES

Tensile Strength (psi)	
Machine Direction	18,000
Transverse Direction	20,000
Elongation (%)	100
Tear Resistance (pli)	1,000
Elastic Modules (psi)	250,000
Coefficient of Friction	.340
Specific Gravity	1.7
Maximum Use Temperature	>614°F/>323°C
Thickness (inches)	0.002
Yield (ft <sup>2</sup> /lb)	54
Color	Natural

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.