

DE-COMP COMPOSITES, INC.

D5300 ETFE

HIGH PERFORMANCE RELEASE FILM

D5300 ETFE is a fluoropolymer film that provides excellent release in critical contour lay-ups.

PROPERTIES

| | | |
|-----------------------------|----|--|
| Tensile Strength (psi) | | 7,000 |
| Elongation (%) | | 300 |
| Tear Resistance (N/mm) | MD | 600 |
| | TD | 400 |
| Melt Point | | 482-518°F 250-270°C |
| Maximum Use Temperature | | 330°F/165°C |
| Thickness (inches) | | 0.001 |
| Yield (ft ² /lb) | | 110 |
| Standard Roll Size | | 48" x 500' 50" x 500' 60" x 600' |
| Color | | Blue |

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.