

DE-COMP COMPOSITES, INC.

D512 Sealant Tape

D512 is designed for use in vacuum bagging. It will maintain an air tight seal during the cure cycle, and then strip clean from the mold during de-bagging. It is formulated without asbestos or solvents.

TYPICAL PROPERTIES	
Maximum Use Temperature	400°F/204°C
Standard Roll Size (t x w x l)	1/8"x1/2"x25'
Rolls per Case	40
Feet per Case	1,000
Color	Gray
Storage	Keep in cool place at or below 80°F/27°C
Shelf Life	12 months from date of manufacture when stored as specified.

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

Page Last Modified: 04/01/2008

Section: Sealant Tapes

RR 4 Box 4460 • Cleveland, Oklahoma 74020 • Phone: 918.358.5881 • Fax: 918.358.3750
E-Mail: email@decomp.com • Web Site: www.decomp.com
Toll Free: 877.609.5088