

DE-COMP COMPOSITES, INC.

D573

Polyester Film with Silicone Adhesive

D573 is used primarily in metal bond and composite shops to break excessive adhesive and to hold materials in place before and during cure cycles. The D573 has excellent tear strength.

PROPERTIES	
Backing Thickness	0.020
Silicone Adhesive thickness	0.0015
Total Thickness (inches)	0.0035
Adhesion	34
Maximum Use Temperature	425°F/219°C
Standard Roll Size	1" x 72 yd 2" x 72 yd
Color	Emerald green

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

Revised Date: 10/15/2009

Section: Tapes

RR 4 Box 4460 • Cleveland, Oklahoma 74020 • Phone: 918.358.5881 • Fax: 918.358.3750
E-Mail: email@decomp.com • Web Site: www.decomp.com
Toll Free: 877.609.5088