

DE-COMP COMPOSITES, INC.

Shrink(1¼ or 2½)

Hi-Shrink Tape



Hi-Shrink tape is a tough, flexible, heat-shrinkable polyester tape. When wrapped around an object and heated, Hi-Shrink tape has the unique ability to shrink and apply pressure. This simple method of applying pressure has advantages in many industries, most specifically, the electrical, defense, and aerospace fields.

The compression force characteristics of Hi-Shrink tape make it an effective and useful tool for the molding and bonding of reinforced plastics. In addition, the tape can be used effectively for compressing, debulking, shaping, forming, and banding of various materials.

PROPERTIES	
Tensile Strength (psi)	>25,000
Melt Point	480°F/249°C
Shrink Initiation	175°F/79°C
Time to Reach Full Shrink at Temperature (min.)	10
Nominal Shrinkage (LD) at 300°F/149°C (%)	20
Maximum Shrink Force (LD (psi)	2,500
Flammability	No Significant Hazard
Auto Ignition Temperature	900°F/482°C
Shelf Life	No Appreciable Aging*
Standard Roll Size	1¼" x 100 yd 2½" x 100 yd

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

Page Last Modified: 08/11/2025

Section: Tapes